





Revision:	Changes:	Date:
1.0	Initial Case	2025.09.02



LED Diagram Circuit

PINOUT ON THE 2ND PAGE

LCM NOTES:

1. LCD TYPE: TRANSMISSIVE, NORMALLY BLACK, IPS
2. RESOLUTION: 1920x1080
3. VIEWING ANGLE: FREE
4. CONTROLLER IC OF MAIN BOARD: RTD2555T
5. VIDEO INTERFACE: HDMI
6. POWER SUPPLY: POWER JACK (6.0-27.0V)
7. MODULE SURFACE LUMINANCE: 1000 cd/m²

GENERAL NOTES:

1. OPERATING TEMPERATURE: -20°C ~ 70°C
2. STORAGE TEMPERATURE: -30°C ~ 80°C
3. WITHOUT INDIVIDUAL TOLERANCE: ±0.3mm[0.012inch]
4. RoHS3 COMPLIANT

PN: RVT156HKHFWN00		
SN:		
DRAWN: M. Stabinski	2025.09.02	1:2.55
CHECKED: M.Wierzbowski	2025.09.02	[mm]
APPR:	ISO A3	P. 1 of 1



EXTERNAL KEYBOARD CONNECTOR - J1			
Pin No.	Desc.	Pin No.	Desc.
1	DOWN	2	UP
3	EXIT	4	MENU
5	PWR	6	LED_EN
7	GND	8	KEYBOARD VDD

BACKLIGHT PWM & POWER - J5			
Pin No.	Desc.	Pin No.	Desc.
1	GND	2	GND
3	EN	4	PWM
5	VDD	6	VDD