



Revision:	Changes:	Date:
1.0	Initial Case	2025.11.13
1.1	Changed PCBA Board & PCBA Gasket	2026.07.21



1.25 MM MOLEX CONNECTORS			1.25 MM MOLEX CONNECTORS		
NO.	TYPE	MATE WITH	NO.	TYPE	MATE WITH
J18 (PWR_EN)	53261-0271	51021-0200	J20 (USB1)	53261-0571	51021-0500
J7 (GPIO2)	53261-0871	51021-0800	J11 (I2C)	53261-0471	51021-0400
J9 (GPIO1)	53261-0871	51021-0800	J8 (SPI/I2C)	53261-0871	51021-0800
J1 (SPEAKER)	53261-0471	51021-0400	J5 (RS422)	53261-0571	51021-0500
J2 (CONSOLE)	53261-0471	51021-0400	J3 (RS232)	53261-0571	51021-0500
J19 (USB2)	53261-0571	51021-0500	J6/J4 (CAN0/CAN1)	53261-0471	51021-0400

LCM NOTES: 1. LCD TYPE: TRANSMISSIVE, NORMALLY BLACK, IPS 2. RESOLUTION: 1280x800 3. VIEWING ANGLE: FREE 4. SUPPLY VOLTAGE FOR MODULE: 7.5V-55V 5. RaspberryPI Compute Module 4		GENERAL NOTES: 1. MODULE SURFACE LUMINANCE:1000 cd/m^2 2. OPERATING TEMPERATURE: -20°C ~ 70°C 3. STORAGE TEMPERATURE: -30°C ~ 80°C 4. WITHOUT INDIVIDUAL TOLERANCE: ±0.3mm[0.012inch] 5. RoHS3 COMPLIANT				
			PN: RVT101HVCFWN00 V1			
			SN:			
			DRAWN: M.Stabinski	2026.07.21	1:1.93	
			CHECKED: M.Wierzbowski	2026.07.21	[mm]	
APPR: M.Wierzbowski		2026.07.21	ISO A3	P. 1 of 1		



LED Diagram Circuit