





Revision:	Changes:	Date:
1.0	Initial Case	2025.11.13
1.1	Changed PCBA Board & PCBA Gasket	2026.07.21
1.2	Changed PCBA Position	2026.09.04



LED Diagram Circuit

1.25 MM MOLEX CONNECTORS			1.25 MM MOLEX CONNECTORS		
NO.	TYPE	MATE WITH	NO.	TYPE	MATE WITH
J18 (PWR_EN)	53261-0271	51021-0200	J20 (USB1)	53261-0571	51021-0500
J7 (GPIO2)	53261-0871	51021-0800	J11 (I2C)	53261-0471	51021-0400
J9 (GPIO1)	53261-0871	51021-0800	J8 (SPI/I2C)	53261-0871	51021-0800
J1 (SPEAKER)	53261-0471	51021-0400	J5 (RS422)	53261-0571	51021-0500
J2 (CONSOLE)	53261-0471	51021-0400	J3 (RS232)	53261-0571	51021-0500
J19 (USB2)	53261-0571	51021-0500	J6/J4 (CAN0/CAN1)	53261-0471	51021-0400

NO.	TYPE	MATE WITH
J17 (POWER)	PTSM 0.5/2-HH1-2.5-THR R16	PTSM 0.5/2-P-2.5

LCM NOTES:
1. LCD TYPE: TRANSMISSIVE, NORMALLY BLACK, IPS
2. RESOLUTION: 1280x800
3. VIEWING ANGLE: FREE
4. SUPPLY VOLTAGE FOR MODULE: 7.5V-55V
5. RaspberryPI Compute Module 4

GENERAL NOTES:
1. MODULE SURFACE LUMINANCE: 1000cd/m^2
2. OPERATING TEMPERATURE: -20°C ~ 70°C
3. STORAGE TEMPERATURE: -30°C ~ 80°C
4. WITHOUT INDIVIDUAL TOLERANCE: ±0.3mm[0.012inch]
5. RoHS3 COMPLIANT

PN: RVT101HVCFWN00 V1
SN:
DRAWN: M.Stabinski 2026.09.03
CHECKED: M.Wierzbowski 2026.09.10
APPR: M.Wierzbowski 2026.09.10