


1.25 MM MOLEX CONNECTORS			1.25 MM MOLEX CONNECTORS		
NO.	TYPE	MATE WITH	NO.	TYPE	MATE WITH
J18 (PWR_EN)	53261-0271	51021-0200	J20 (USB1)	53261-0571	51021-0500
J7 (GPIO2)	53261-0871	51021-0800	J11 (I2C)	53261-0471	51021-0400
J9 (GPIO1)	53261-0871	51021-0800	J8 (SPI/I2C)	53261-0871	51021-0800
J1 (SPEAKER)	53261-0471	51021-0400	J5 (RS422)	53261-0571	51021-0500
J2 (CONSOLE)	53261-0471	51021-0400	J3 (RS232)	53261-0571	51021-0500
J19 (USB2)	53261-0571	51021-0500	J6/J4 (CAN0/CAN1)	53261-0471	51021-0400



NO.	TYPE	MATE WITH
J17 (POWER)	PTSM 0.5/2-HH1-2.5-THR R16	PTSM 0.5/2-P-2.5

LCD NOTES:

- LCD TYPE: TRANSMISSIVE, NORMALLY BLACK, IPS
- RESOLUTION: 1280x800
- VIEWING ANGLE: FREE
- SUPPLY VOLTAGE FOR MODULE: 7.5V-55V
- RaspberryPI Compute Module 4

GENERAL NOTES:

- MODULE SURFACE LUMINANCE: 1000 cd/m²
- OPERATING TEMPERATURE: -20°C ~ 70°C
- STORAGE TEMPERATURE: -30°C ~ 80°C
- WITHOUT INDIVIDUAL TOLERANCE: ±0.3mm[0.012inch]
- RoHS3 COMPLIANT

PN: RVT101HVCFWN00			
SN:			
DRAWN: M.Stabinski	2025.11.13	1:1.82	
CHECKED: C.Gao	2025.11.13	[mm]	
APPR: M.Wierzbowski	2025.11.13	ISO A3	