



## TFT MODULE SPECIFICATION

### **RVT101HVUNWC00**

HB, IPS, USB C 10.1" LCD TFT display datasheet  
Rev. 1.1  
2025-11-14

---

**Riverdi Sp. z o.o.**

Nowy Swiat 36  
80-299 Gdansk, Poland  
VAT ID: PL5842767153  
Registration number (KRS): 0000923967

**+48 587 703 116**

Office hours: 9:00 to 17:30 CET (Mon-Fri)

**[contact@riverdi.com](mailto:contact@riverdi.com)**

**[riverdi.com](https://riverdi.com)**

| ITEM                           | CONTENTS                              | UNIT              |
|--------------------------------|---------------------------------------|-------------------|
| LCD Type                       | TFT/Transmissive/Normally Black/IPS   | /                 |
| Size                           | 10.1                                  | Inch              |
| Viewing Direction              | Free                                  | /                 |
| Outside Dimensions (W x H x D) | 257.96 x 168.60 x 12.88               | mm                |
| Active Area (W x H)            | 216.96 x 135.60                       | mm                |
| Pixel Pitch (W x H)            | 0.1695 x 0.1695                       | mm                |
| Resolution                     | 1280 (RGB) x 800                      | /                 |
| Brightness                     | 800                                   | cd/m <sup>2</sup> |
| Color Depth                    | 16.7 M                                | /                 |
| Pixel Arrangement              | RGB Vertical Stripe                   | /                 |
| Controller of the main board   | LT7911D                               | /                 |
| Interface                      | USB-C                                 | /                 |
| With/Without Touch             | With Projected Capacitive Touch Panel | /                 |
| CTP Driver                     | ILI2132A                              | /                 |
| Touch Panel Interface          | USB-C                                 | /                 |
| Power Supply                   | USB-C (5.0V)                          | V                 |
| Weight                         | 482                                   | g                 |

**Note 1.** RoHS3 compliant

**Note 2.** LCM weight tolerance: ± 5%.

## 1. REVISION RECORD

| REV NO. | REV DATE   | CONTENTS                         | REMARKS |
|---------|------------|----------------------------------|---------|
| 1.0     | 2025-05-23 | Initial release                  |         |
| 1.1     | 2025-11-14 | Changed PCBA position on drawing |         |

## 2. CONTENTS

|      |                                                    |    |
|------|----------------------------------------------------|----|
| 1.   | REVISION RECORD .....                              | 3  |
| 2.   | CONTENTS .....                                     | 4  |
| 3.   | MODULE CLASSIFICATION INFORMATION .....            | 5  |
| 4.   | ASSEMBLY .....                                     | 6  |
| 4.1  | uxTouch Assembly .....                             | 6  |
| 5.   | MODULE DRAWING .....                               | 7  |
| 6.   | ABSOLUTE MAXIMUM RATINGS .....                     | 8  |
| 7.   | ELECTRICAL CHARACTERISTICS .....                   | 8  |
| 8.   | BACKLIGHT ELECTRICAL CHARACTERISTICS .....         | 9  |
| 9.   | ELECTRO-OPTICAL CHARACTERISTICS .....              | 10 |
| 10.  | INTERFACES DESCRIPTION .....                       | 13 |
| 10.1 | PCB overview .....                                 | 13 |
| 10.2 | USB interface (P9, P10) .....                      | 14 |
| 10.3 | Video/Touch panel interface - USB-C .....          | 14 |
| 10.4 | External keyboard - P6 .....                       | 15 |
| 10.5 | Backlight PWM & Power - P5 .....                   | 15 |
| 10.6 | Speaker - P4 .....                                 | 16 |
| 10.7 | I2C - P11, P12 .....                               | 16 |
| 11.  | DISPLAY SPECIFICATION .....                        | 16 |
| 12.  | CaPACITIVE TOUCH SCREEN PANEL SPECIFICATIONS ..... | 17 |
| 12.1 | Mechanical characteristics .....                   | 17 |
| 12.2 | Electrical characteristics .....                   | 17 |
| 13.  | INSPECTION .....                                   | 18 |
| 13.1 | Inspection condition .....                         | 18 |
| 13.2 | Inspection standard .....                          | 19 |
| 14.  | RELIABILITY TEST .....                             | 21 |
| 15.  | LEGAL INFORMATION .....                            | 22 |
| 16.  | CONTACT .....                                      | 23 |

### 3. MODULE CLASSIFICATION INFORMATION


| RV | T  | 101 | H  | V  | U  | N  | W  | C  | 00  |
|----|----|-----|----|----|----|----|----|----|-----|
| 1. | 2. | 3.  | 4. | 5. | 6. | 7. | 8. | 9. | 10. |

| NO. | PARAMETER        | SYMBOL                           |
|-----|------------------|----------------------------------|
| 1.  | BRAND            | RV – Riverdi                     |
| 2.  | PRODUCT TYPE     | T – TFT Standard                 |
| 3.  | DISPLAY SIZE     | 101 – 10.1”                      |
| 4.  | MODEL SERIAL NO. | H – High Brightness, IPS         |
| 5.  | RESOLUTION       | V – 1280 x 800 px                |
| 6.  | INTERFACE        | U – USB C                        |
| 7.  | FRAME            | N – Without Mounting Metal Frame |
| 8.  | BACKLIGHT TYPE   | W – LED White                    |
| 9.  | TOUCH PANEL      | C – uxTouch                      |
| 10. | VERSION          | 00 – version                     |

## 4. ASSEMBLY


### 4.1 uxTouch Assembly

uxTouch are LCD TFT displays with specially designed projected capacitive touch panels. uxTouch display can be mounted without any additional holes in the housing. Our standard uxTouch displays include double-sided adhesive tape (DST) to stick TFT easily to the housing. uxTouch models with double-side adhesive tape can be mounted by fastening the glass to the housing.







*Figure 1. General view of the module*

| Revision: | Changes:                            | Date:      |
|-----------|-------------------------------------|------------|
| 1.0       | Initial Case                        | 2025.04.11 |
| 1.1       | Moved the PCB, added grounding tape | 2025.05.21 |
| 1.2       | Changed PCBA Position               | 2025.11.14 |



BLACK MASK PRINTING  
Reffer to RAL9005



LED Diagram Circuit

PINOUT ON THE 2ND PAGE

|                                                                                                                                                                                                  |                                                                                                                                                            |                                                                                                                                                                                                                                                                |                          |            |                                                                                       |                                                                                       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>LCD NOTES:</b><br>1. LCD TYPE: TRANSMISSIVE, NORMALLY BLACK, IPS<br>2. RESOLUTION: 1280x800<br>3. VIEWING ANGLE: FREE<br>4. CONTROLLER IC OF MAIN BOARD: LT7911D<br>5. VIDEO INTERFACE: USB-C | <b>TP NOTES:</b><br>1. TP STRUCTURE: G+G<br>2. CG THICKNESS: 1.10mm[0.043inch]<br>3. SURFACE HARDNESS: 7H<br>4. DRIVER IC: ILI2132A<br>5. INTERFACE: USB-C | <b>GENERAL NOTES:</b><br>1. MODULE SURFACE LUMINANCE:800 cd/m^2<br>2. OPERATING TEMPERATURE: -20°C ~ 70°C<br>3. STORAGE TEMPERATURE: -30°C ~ 80°C<br>4. WITHOUT INDIVIDUAL TOLERANCE:<br>±0.3mm[0.012inch]<br>5. USB-C Power supply 5.0V<br>6. RoHS3 COMPLIANT |                          |            |  |                                                                                       |
|                                                                                                                                                                                                  |                                                                                                                                                            |                                                                                                                                                                                                                                                                | PN: RVT101HVUNWC00       |            |                                                                                       |                                                                                       |
|                                                                                                                                                                                                  |                                                                                                                                                            |                                                                                                                                                                                                                                                                | SN:                      |            |                                                                                       |                                                                                       |
|                                                                                                                                                                                                  |                                                                                                                                                            |                                                                                                                                                                                                                                                                | DRAWN: M.Stabinski       | 2025.11.14 | 1:2.03                                                                                |  |
|                                                                                                                                                                                                  |                                                                                                                                                            |                                                                                                                                                                                                                                                                | CHECKED: J.Teska-Adamiec | 2025.11.14 | [mm]                                                                                  |                                                                                       |
| APPR: M.Wierzbowski                                                                                                                                                                              | 2025.11.14                                                                                                                                                 | ISO A3                                                                                                                                                                                                                                                         | P. 1 of 1                |            |                                                                                       |                                                                                       |

## 6. ABSOLUTE MAXIMUM RATINGS

| PARAMETER                               | SYMBOL          | MIN  | MAX | UNIT |
|-----------------------------------------|-----------------|------|-----|------|
| Supply Voltage for Module               | V <sub>DD</sub> | -0.5 | 5.5 | V    |
| Operating Temperature                   | T <sub>OP</sub> | -20  | 70  | °C   |
| Storage Temperature                     | T <sub>ST</sub> | -30  | 80  | °C   |
| Storage Humidity (@ 25 ± 5°C)           | H <sub>ST</sub> | 10   | -   | % RH |
| Operating Ambient Humidity (@ 25 ± 5°C) | H <sub>OP</sub> | 10   | -   | % RH |

**Note.** The above are maximum values. If exceeded, they may cause permanent damage to the unit.

## 7. ELECTRICAL CHARACTERISTICS

| PARAMETER                 | SYMBOL          | MIN | TYP | MAX | UNIT | NOTE |
|---------------------------|-----------------|-----|-----|-----|------|------|
| Supply Voltage for Module | V <sub>DD</sub> | 4.7 | 5.0 | 5.3 | V    |      |

| PARAMETER                                | SYMBOL           | BL 0% | BL 50 % | BL 100% | UNIT | NOTE   |
|------------------------------------------|------------------|-------|---------|---------|------|--------|
| Current drawn from V <sub>DD</sub> @5.0V | I <sub>VDD</sub> | 430   | 1115    | 1660    | mA   | Note 3 |

**Note 1.**

BL 0%, current was measured with BL brightness set to 0%,  
 BL 50%, current was measured with BL brightness set to 50%,  
 BL 100%, current was measured with BL brightness set to 100%.

Values of current may vary due to type of used cable.

## 8. BACKLIGHT ELECTRICAL CHARACTERISTICS

| PARAMETER                   | SYMBOL | MIN | TYP    | MAX | UNIT  | NOTE   |
|-----------------------------|--------|-----|--------|-----|-------|--------|
| Backlight Power Consumption | WBL    | -   | 5,76   | -   | W     |        |
| Lifetime                    | -      | -   | 50,000 | -   | hours | Note 1 |

**Note 1.** Unless specified, the ambient temperature  $T_a = 25^{\circ}\text{C}$

**Note 2.** The recommended operating conditions refer to a range in which operation of this product is guaranteed. The operation cannot be guaranteed if the absolute maximum values exceed.

**Note 3.** If LED is driven by high current, high ambient temperature and humidity condition, the lifetime of LED will be reduced. Operating life means brightness goes down to 50% initial brightness. Typical operating lifetime is estimated data.

## 9. ELECTRO-OPTICAL CHARACTERISTICS

| ITEM                       | SYMBOL   | CONDITION                                      | MIN  | TYP  | MAX  | UNIT              | RMK    | NOTE |
|----------------------------|----------|------------------------------------------------|------|------|------|-------------------|--------|------|
| Response Time              | Tr+Tf    | $\theta=0^\circ$<br>$\phi=0^\circ$<br>Ta=25 °C | -    | 25   | 35   | ms                | FIG 1. | 4, 7 |
| Contrast Ratio             | Cr       |                                                | -    | 800  | 1000 | ---               | FIG 2. | 1, 7 |
| Surface Luminance          | Lv       |                                                | -    | 800  | -    | cd/m <sup>2</sup> |        | 2, 7 |
| Viewing Angle Range        | $\theta$ | $\phi = 90^\circ$                              | 75   | 85   | -    | deg               | FIG 3. | 6    |
|                            |          | $\phi = 270^\circ$                             | 75   | 85   | -    | deg               |        |      |
|                            |          | $\phi = 0^\circ$                               | 75   | 85   | -    | deg               |        |      |
|                            |          | $\phi = 180^\circ$                             | 75   | 85   | -    | deg               |        |      |
| CIE (x, y)<br>Chromaticity | Rx       | $\theta=0^\circ$<br>$\phi=0^\circ$<br>Ta=25 °C | 0.22 | 0.26 | 0.30 | -                 | FIG 2. | 5,7  |
|                            | Ry       |                                                | 0.20 | 0.24 | 0.28 | -                 |        |      |
|                            | Gx       |                                                | 0.34 | 0.38 | 0.42 | -                 |        |      |
|                            | Gy       |                                                | 0.50 | 0.54 | 0.58 | -                 |        |      |
|                            | Bx       |                                                | 0.10 | 0.14 | 0.18 | -                 |        |      |
|                            | By       |                                                | 0.09 | 0.13 | 0.17 | -                 |        |      |
|                            | Wx       |                                                | 0.28 | 0.32 | 0.36 | -                 |        |      |
|                            | Wy       |                                                | 0.29 | 0.33 | 0.37 | -                 |        |      |

**Note 1.** Contrast Ratio (CR) is defined mathematically as below, for more information see Figure 2.

$$\text{Contrast Ratio} = \frac{\text{Average Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}{\text{Average Surface Luminance with all black pixels (P1, P2, P3, P4, P5)}}$$

**Note 2.** Surface luminance is the LCD surface from the surface with all pixels displaying white. For more information see Figure 2.

$$L_v = \text{Average Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}$$

**Note 3.** The uniformity in surface luminance  $\delta$  WHITE is determined by measuring luminance at each test position 1 through 5, and then dividing the minimum luminance of 5 points luminance by maximum luminance of 5 points luminance. For more information see Figure 2.

$$\delta \text{ WHITE} = \frac{\text{Minimum Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}{\text{Maximum Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}$$

**Note 4.** Response time is the time required for the display to transition from white to black (Rise Time,  $T_r$ ) and from black to white (Decay Time,  $T_f$ ). For additional information see Figure 1. The test equipment is BM-7A.

**Note 5.** CIE (x, y) chromaticity, the x, y value is determined by measuring luminance at each test position 1 through 5, and then make average value.

**Note 6.** For TFT module, viewing angle is the angle at which the contrast ratio is greater 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to LCD surface. For more information see Figure 3.

**Note 7.** Viewing angle is measured at the center point of the LCD by CONOSCOPE (ergo-80). For response time testing, the testing data is based on BM-7A. Instruments for Contrast Ratio, Surface Luminance, Luminance Uniformity, Chromaticity the test data is based on SR-3A.




Figure 2. The definition of response time




Figure 3. Measuring method for Contrast ratio, surface luminance, Luminance uniformity, CIE (x, y) chromaticity





Figure 4. The definition of viewing angle

## 10. INTERFACES DESCRIPTION

### 10.1 PCB overview



| NAME                     | CONNECTOR                         | DESCRIPTION                                                                                                                                                                                                                  | NOTE |
|--------------------------|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| P9, P10                  | USB                               | USB molex                                                                                                                                                                                                                    |      |
| VIDEO/<br>TOUCH<br>PANEL | USB-C                             | Video interface/Touch panel interface                                                                                                                                                                                        |      |
| P6                       | External<br>keyboard<br>connector | Molex 53261-0871 or alternative; Horizontal, 1.25mm pitch;<br>8 pins. The connector is reserved for external keyboard.                                                                                                       |      |
| P5                       | Backlight<br>PWM &<br>Power       | Molex 53261-0671 or alternative; Horizontal, 1.25mm pitch;<br>6 pins.<br><br>The unit realizes the function of digital dimming. This connector enables to control backlight PWM externally.<br><br>Alternative power supply. |      |
| P4                       | Speaker                           | Speaker molex                                                                                                                                                                                                                |      |
| P11, P12                 | I2C                               | I2C molex                                                                                                                                                                                                                    |      |

Note 1. External keyboards are optional, not included in the standard kit.

## 10.2 USB interface (P9, P10)

| PIN      | SYMBOL | DESCRIPTION        |
|----------|--------|--------------------|
| <b>1</b> | VBUS   | Power supply, 5.0V |
| <b>2</b> | USB_N  | USB_D-             |
| <b>3</b> | USB_P  | USB_D+             |
| <b>4</b> | GND    | Ground             |

## 10.3 Video/Touch panel interface – USB-C

| PIN            | SYMBOL        | DESCRIPTION                                     |
|----------------|---------------|-------------------------------------------------|
| <b>A4/B4</b>   | VBUSA/VBUSB   | Power supply, 5.0V                              |
| <b>A9/B9</b>   | VBUSA/VBUSB   | Power supply, 5.0V                              |
| <b>A2/B2</b>   | SSTXP1/SSTXP2 | Super speed differential pair transmit positive |
| <b>A3/B3</b>   | SSTXN1/SSTXN2 | Super speed differential pair transmit negative |
| <b>A5/B5</b>   | CC1/CC2       | Configuration channel                           |
| <b>A6/B6</b>   | DP1/DP2       | Differential pair positive                      |
| <b>A7/B7</b>   | DN1/DN2       | Differential pair negative                      |
| <b>A8/B8</b>   | SBU1/SBU2     | Sideband use                                    |
| <b>A10/B10</b> | SSRXN2/SSRXN1 | Super speed differential pair receive positive  |
| <b>A11/B11</b> | SSRXP2/SSRXP1 | Super speed differential pair receive positive  |
| <b>A1/B1</b>   | GND           | Ground                                          |
| <b>A12/B12</b> | GND           | Ground                                          |

**Note 1.** All the signals in Touch panel connector are in accordance with USB-C standard.

**Note 2.** Matched Riverdi cable accessory: USB-A 2.0 TO USB-C CABLE

## 10.4 External keyboard – P6

| PIN | SYMBOL | DESCRIPTION                         |
|-----|--------|-------------------------------------|
| 1   | INP1   | Backlight level rise                |
| 2   | INP2   | Backlight level decrease            |
| 3   | INP3   | Switch Input 3 – reserved, not used |
| 4   | INP4   | Switch Input 4 – reserved, not used |
| 5   | INP5   | Switch Input 5 – reserved, not used |
| 6   | INP6   | Switch Input 6 – reserved, not used |
| 7   | GND    | Ground                              |
| 8   | VCC    | Power supply, 3.3V                  |

**Note.** External keyboard is by default to change backlight brightness level.

## 10.5 Backlight PWM & Power – P5

| PIN | SYMBOL   | DESCRIPTION             | NOTE      |
|-----|----------|-------------------------|-----------|
| 1   | GND      | Ground                  |           |
| 2   | GND      | Ground                  |           |
| 3   | EXT_DIMM | External dimming        | Note 1, 3 |
| 4   | EXT_EN   | External dimming enable | Note 3    |
| 5   | VIN2     | Power supply, 6-36V     | Note 2    |
| 6   | VIN2     | Power supply, 6-36V     | Note 2    |

**Note 1.** PWM frequency range: 100Hz - 10kHz.

100% PWM duty cycle corresponds to maximum brightness

0% PWM duty cycle corresponds to minimum brightness

**Note 2.** Matched Riverdi cable accessory: RVA-0106M-1.25FF-1.

**Note 3.** Notice

$V_L < 1.2V$  = active low

$V_H > 2.4V \dots 36V$  = active high

Socket used for external power supply.

## 10.6 Speaker – P4

| PIN | SYMBOL | DESCRIPTION               | NOTE |
|-----|--------|---------------------------|------|
| 1   | OUTP   | Speaker coil „+” terminal |      |
| 2   | OUTN   | Speaker coil „-” terminal |      |

**Note.** Max available power for connected speaker 3W (4Ω).

## 10.7 I2C – P11, P12

| PIN | SYMBOL  | DESCRIPTION        | NOTE |
|-----|---------|--------------------|------|
| 1   | VBUS    | Power supply, 5.0V |      |
| 2   | SCL     | Serial clock       |      |
| 3   | SDA     | Serial data        |      |
| 4   | GND     | Ground             |      |
| 10  | I2C_SDA | I2C_Data signal    | NC   |

## 11. DISPLAY SPECIFICATION

The TFT of the module applies Riverdi high brightness, IPS, 10.1” LVDS: RVT101HVLNWC00

The supported resolution of the display in this module is 1280\*800.

For detailed information, please refer to datasheet of display.

## 12. CAPACITIVE TOUCH SCREEN PANEL SPECIFICATIONS

### 12.1 Mechanical characteristics

| DESCRIPTION                     | SPECIFICATION         | REMARK |
|---------------------------------|-----------------------|--------|
| <b>Touch Panel Size</b>         | 10.1 inch             | αTouch |
| <b>Outline Dimension of CTP</b> | 228.46 mm x 148.10 mm |        |
| <b>Product Thickness</b>        | 2.35 mm               |        |
| <b>Glass Thickness</b>          | 1.1 mm                |        |
| <b>CTP View Area</b>            | 217.96 mm x 136.60 mm |        |
| <b>Sensor Active Area</b>       | 216.96 mm x 135.60 mm |        |
| <b>Surface Hardness</b>         | 7H                    |        |

### 12.2 Electrical characteristics

| DESCRIPTION       | SPECIFICATION | REMARK |
|-------------------|---------------|--------|
| <b>Linearity</b>  | +/-1.5mm      |        |
| <b>Controller</b> | ILI2132A      |        |
| <b>Resolution</b> | 1280 x 800    |        |

## 13. INSPECTION

Standard acceptance/rejection criteria for TFT module


### 13.1 Inspection condition

Ambient conditions:



- Temperature:  $25 \pm 2^{\circ}\text{C}$
- Humidity:  $(60 \pm 10) \% \text{RH}$
- Illumination: Single fluorescent lamp non-directive (300 to 700 lux)

Viewing distance:  $35 \pm 5\text{cm}$  between inspector bare eye and LCD.

Viewing Angle: U/D:  $45^{\circ}/45^{\circ}$ , L/R:  $45^{\circ}/45^{\circ}$



## 13.2 Inspection standard

| ITEM                                                                   | CRITERION                                                                                                                |                                          |                                     |
|------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|------------------------------------------|-------------------------------------|
| Black spots, white spots, light leakage, Foreign Particle (round Type) | <br>$D=(x+y)/2$<br>Spots density: 10 mm | Size = 10.1"                             |                                     |
|                                                                        |                                                                                                                          | Average Diameter                         | Qualified Qty                       |
|                                                                        |                                                                                                                          | $D \leq 0.2 \text{ mm}$                  | Ignored                             |
|                                                                        |                                                                                                                          | $0.2 \text{ mm} < D \leq 0.3 \text{ mm}$ | $N \leq 4$                          |
|                                                                        |                                                                                                                          | $0.5 \text{ mm} < D$                     | Not allowed                         |
| LCD black spots, white spots, light leakage (line Type)                | <br>Spots density: 10 mm              | Size = 10.1"                             |                                     |
|                                                                        |                                                                                                                          | Length                                   | Width Qualified Qty                 |
|                                                                        |                                                                                                                          | -                                        | $W \leq 0.05$ Ignored               |
|                                                                        |                                                                                                                          | $L \leq 5.0$                             | $0.05 < W \leq 0.1$ $N \leq 3$      |
|                                                                        |                                                                                                                          | $5.0 < L$                                | $0.10 < W$<br>$5.0 < L$ Not allowed |
| Bright/Dark Dots                                                       | Size = 10.1"                                                                                                             |                                          |                                     |
|                                                                        | Item                                                                                                                     | Qualified Qty                            |                                     |
|                                                                        | Bright dots                                                                                                              | 0                                        |                                     |
|                                                                        | Dark dots                                                                                                                | 0                                        |                                     |
|                                                                        | Cluster bright dots or dark dots                                                                                         | 0                                        |                                     |
|                                                                        | Total bright and dark dots                                                                                               | 0                                        |                                     |

|                                |                      |                   |               |
|--------------------------------|----------------------|-------------------|---------------|
| Clear spots                    | Size $\geq 5.0''$    |                   |               |
|                                | Average Diameter     |                   | Qualified Qty |
|                                | D < 0.2 mm           |                   | Ignored       |
|                                | 0.2 mm < D < 0.3 mm  |                   | 4             |
|                                | 0.3 mm < D < 0.5 mm  |                   | 2             |
|                                | 0.5 mm < D           |                   | 0             |
|                                | Spots density: 10 mm |                   |               |
| Touch panel spots              | Size $\geq 5.0''$    |                   |               |
|                                | Average Diameter     |                   | Qualified Qty |
|                                | D < 0.25 mm          |                   | Ignored       |
|                                | 0.25 mm < D < 0.5 mm |                   | 4             |
|                                | 0.5 mm < D           |                   | 0             |
| Touch panel white line scratch | Size $\geq 5.0''$    |                   |               |
|                                | Length               | Width             | Qualified Qty |
|                                | -                    | $W \leq 0.03$     | Ignored       |
|                                | $L \leq 5.0$         | $0.03 < W < 0.05$ | 2             |
|                                | -                    | $0.05 < W$        | 0             |

## 14. RELIABILITY TEST

| NO. | TEST ITEM                           | TEST CONDITION                                                                                                                       | NOTE   |
|-----|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|--------|
| 1   | High Temperature Storage            | 80°C/120 hours                                                                                                                       | Note 1 |
| 2   | Low Temperature Storage             | -30°C/120 hours                                                                                                                      |        |
| 3   | High Temperature Operating          | 70°C/120 hours                                                                                                                       |        |
| 4   | Low Temperature Operating           | -20°C/120 hours                                                                                                                      |        |
| 5   | High Temperature and High Humidity  | 40°C, 90%RH, 120Hrs                                                                                                                  |        |
| 6   | Thermal Cycling Test (No operation) | -20°C for 30min, 70°C for 30 min.<br>100 cycles. Then test at room temperature after 1 hour                                          | Note 2 |
| 7   | Vibration Test                      | Frequency: 10 ÷ 55 Hz.<br>Stroke: 1.5 mm.<br>Sweep: 10Hz ÷ 55Hz ÷ 10 Hz.<br>2 hours for each direction of X, Y, Z<br>(Total 6 hours) |        |

**Note 1.** Sample quantity for each test item is 5 ÷ 10 pcs.

**Note 2.** The device is kept at room temperature for 2 hours prior to starting the test

## 15. LEGAL INFORMATION

CE marking is usually obligatory only for a complete end product. Riverdi display modules are semi-finished goods which are used as inputs to become part of the finished products.

Therefore, Riverdi display modules are not CE marked.

This is not a standalone product. It was designed as an electronic component. It needs integration with a whole system to be fully functional.

Riverdi grants the guarantee for the proper operation of the goods for a period of 12 months from the date of possession of the goods. If in a consequence of this guaranteed execution the customer has received the defects-free item as replacement for the defective item, the effectiveness period of this guarantee shall start anew from the moment the customer receives the defects-free item.

Information about device is the property of Riverdi and may be the subject of patents pending or granted. It is not allowed to copy or disclosed this document without prior written permission.

Riverdi endeavors to ensure that all contained information in this document is correct but does not accept liability for any error or omission. Riverdi products are in developing process and published information may be not up to date. Riverdi reserves the right to update and makes changes to Specifications or written material without prior notice at any time. It is important to check the current position with Riverdi.

Images and graphics used in this document are only for illustrative the purpose. All images and graphics are possible to be displayed on the range products of Riverdi, however the quality may vary. Riverdi is no liable to the buyer or to any third party for any indirect, incidental, special, consequential, punitive, or exemplary damages (including without limitation lost profits, lost savings, or loss of business opportunity) relating to any product, service provided or to be provided by Riverdi, or the use or inability to use the same, even if Riverdi has been advised of the possibility of such damages.

Riverdi products are not fault tolerant nor designed, manufactured or intended for use or resale as on line control equipment in hazardous environments requiring fail-safe performance, such as in the operation of nuclear facilities, aircraft navigation or communication systems, air traffic control, direct life support machines or weapons systems in which the failure of the product could lead directly to death, personal injury or severe physical or environmental damage ('High-Risk Activities'). Riverdi and its suppliers specifically disclaim any expressed or implied warranty of fitness for High-Risk Activities. Using Riverdi products and devices in 'High-Risk Activities' and in any other application is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Riverdi from all damages, claims or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Riverdi intellectual property rights.

## 16. CONTACT

### Your Success is Our Priority

Stuck on a technical challenge? Need expert guidance?  
Our dedicated support team is just a message away.

Contact us at  
[contact@riverdi.com](mailto:contact@riverdi.com)

We're here to ensure your project's success, every step of the way!