




Revision:	Changes:	Date:
1.0	Initial Case	2025.04.11
1.1	Added grounding tape	2025.05.21
1.2	Changed Position Of PCBA	2025.11.14



LED Diagram Circuit

PINOUT ON THE 2ND PAGE

LCD NOTES: 1. LCD TYPE: TRANSMISSIVE, NORMALLY BLACK, IPS 2. RESOLUTION: 1280x800 3. VIEWING ANGLE: FREE 4. CONTROLLER IC OF MAIN BOARD: LT7911D 5. VIDEO INTERFACE: USB-C 6. ZERO BAD PIXEL		GENERAL NOTES: 1. SURFACE LUMINANCE:1000cd/m^2 2. OPERATING TEMPERATURE: -20°C ~ 70°C 3. STORAGE TEMPERATURE: -30°C ~ 80°C 4. WITHOUT INDIVIDUAL TOLERANCE: ±0.3mm[0.012inch] 5. USB-C Power supply 5.0V 6. RoHS3 COMPLIANT				
			PN: RVT101HVUNWN00			
			SN:			
			DRAWN: M.Stabinski	2025.11.14	1:1.64	
			CHECKED: J.Teska-Adamiec	2025.11.14	[mm]	
APPR: M.Wierzbowski	2025.11.14	ISO A3	P. 1 of 1			



EXTERNAL KEYBOARD CONNECTOR - P6			
Pin No.	Desc.	Pin No.	Desc.
1	DOWN	2	UP
3	EXIT	4	MENU
5	PWR	6	LED_EN
7	GND	8	KEYBOARD VDD

BACKLIGHT PWM & POWER - P5			
Pin No.	Desc.	Pin No.	Desc.
1	GND	2	GND
3	EN	4	PWM
5	VDD	6	VDD