





Revision:	Changes:	Date:
1.0	Initial Case	2025.09.02
1.1	PCBA Position & Gasket Change	2026.01.29



PINOUT ON THE 2ND PAGE

**LCM NOTES:**  
 1. LCD TYPE: TRANSMISSIVE, NORMALLY BLACK, IPS  
 2. RESOLUTION: 1920x1080  
 3. VIEWING ANGLE: FREE  
 4. CONTROLLER IC OF MAIN BOARD: RTD2555T  
 5. VIDEO INTERFACE: HDMI  
 6. POWER SUPPLY: POWER JACK (6.0-27.0V)  
 7. MODULE SURFACE LUMINANCE: 1000 cd/m<sup>2</sup>

**GENERAL NOTES:**  
 1. OPERATING TEMPERATURE: -20°C ~ 70°C  
 2. STORAGE TEMPERATURE: -30°C ~ 80°C  
 3. WITHOUT INDIVIDUAL TOLERANCE:  
 ±0.3mm[0.012inch]  
 4. RoHS3 COMPLIANT

PN: RVT156HKHNWN00		DRAWN: M.Stabinski	2026.01.29	1:2.49	
SN:					
CHECKED: C.Gao			2026.01.29	[mm]	
APPR: M.Wierzbowski			2026.01.29	ISO A3	P. 1 of 1



#### EXTERNAL KEYBOARD CONNECTOR - J1

Pin No.	Desc.	Pin No.	Desc.
1	DOWN	2	UP
3	EXIT	4	MENU
5	PWR	6	LED_EN
7	GND	8	KEYBOARD VDD

#### BACKLIGHT PWM & POWER - J5

Pin No.	Desc.	Pin No.	Desc.
1	GND	2	GND
3	EN	4	PWM
5	VDD	6	VDD