





PINOUT ON THE 2ND PAGE

TFT NOTES: 1. LCD TYPE: TRANSMISSIVE, NORMALLY BLACK, IPS 2. RESOLUTION: 800x480 3. VIEWING ANGLE: FREE 4. CONTROLLER IC OF MAIN BOARD: TFP401APZPR 5. VIDEO INTERFACE: HDMI 6. POWER SUPPLY: POWER JACK (7.0-36.0V); USB-C.	TP NOTES: 1. TP STRUCTURE: G+G 2. CG THICKNESS: 1.10mm[0.043inch] 3. DRIVER IC: ILI2132A 4. INTERFACE: USB-C 5. SURFACE HARDNESS: 7H	GENERAL NOTES: 1. SURFACE LUMINANCE: 800cd/m ² 2. OPERATING TEMPERATURE: -20°C ~ 70°C 3. STORAGE TEMPERATURE: -30°C ~ 80°C 4. WITHOUT INDIVIDUAL TOLERANCE: ±0.3mm 5. RoHS COMPLIANT				
			PN: RVT50HQHNWCA0 V2.0A			
			SN:			
			DRAWN: M.Stabinski	2026.03.23	1:1.09	
			CHECKED: M.Wierzbowski	2026.03.23	[mm]	
APPR: M.Wierzbowski	2026.03.23	ISO A3	P. 1 of 1			



BACKLIGHT PWM & POWER - CN1			
Pin No.	Desc.	Pin No.	Desc.
1	VDD	2	VDD
3	PWM	4	EN
5	GND	6	GND